SECTION 102800 TOILET, BATH, AND LAUNDRY ACCESSORIES - ASI

PART 1 GENERAL

1.01 SECTION INCLUDES

A. Soap and hand sanitizer dispensers.

1.02 RELATED REQUIREMENTS

1.03 REFERENCE STANDARDS

1.04 SUBMITTALS

- A. See Section 013000 Administrative Requirements for submittal procedures.
- B. Manufacturer's Installation Instructions: Indicate special procedures and conditions requiring special attention.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Basis of Design Manufacturer: American Specialties, Inc: www.americanspecialties.com/#sle.
- B. Other Acceptable Manufacturers:
 - Products by listed manufacturers are subject to compliance with specified requirements found in specification and in Technical Data Sheet of selected ASI model and prior approval of Architect.
- C. Substitutions: See Section 016000 Product Requirements.
 - All proposed substitutions (clearly delineated as such) must be submitted in writing for approval by Architect minimum of 10 working days prior to bid date and must be made available to all bidders. Proposed substitutes must be accompanied by review of specification and ASI Technical Data Sheets noting compliance on line-by-line basis.

2.02 SOAP AND HAND SANITIZER DISPENSERS

- A. Soap Dispenser: Liquid soap dispenser, with stainless steel cover and horizontal stainless steel tank and working parts; push type soap valve, check valve, and window gauge refill indicator, tumbler lock.
 - 1. Mounting: As indicated in product listing.
 - 2. Minimum Capacity: As indicated in product listing.
 - Products:
 - Model 0347 Satin Stainless Steel Finish Soap Dispenser Liquid, Vertical Valve -40 oz (1.18 L) - Surface-mounted.
 - b. Substitutions: Section 016000 Product Requirements.

2.03 MATERIALS

A. Accessories - General: Shop assembled, free of dents and scratches and packaged complete with anchors and fittings, steel anchor plates, adapters, and anchor components for installation.

The paragraph below is optional text

2.04 FABRICATION

2.05 FINISHES

The paragraph below is optional text

- A. Shop Primed Ferrous Metals: Pretreat and clean, spray apply one coat primer and bake. *The paragraph below is optional text*
 - B. Back paint components where contact is made with building finishes to prevent electrolysis.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify existing conditions before starting work.
- B. Verify exact location of accessories for installation.

3.02 PREPARATION

- A. Deliver inserts and rough-in frames to site for timely installation.
- B. Provide templates and rough-in measurements as required.

3.03 INSTALLATION

A. Install accessories in accordance with manufacturers' instructions in locations indicated on drawings.

The paragraph below is optional text

- B. Mounting Heights: As required by accessibility regulations, unless otherwise indicated.
 - 1. Other Accessories: As indicated on drawings.

3.04 PROTECTION

A. Protect installed accessories from damage due to subsequent construction operations.

END OF SECTION